

### URSA FDP 2/Vr

MW-EN-13162-T3-MU1-WL(P)-AFr5

Fasadne izolacijske ploče izrađene od mineralne staklene vune – vodoodbojne, jednostrano kaširane crnim armiranim staklenim voalom.

Toplinska i zvučna izolacija ventiliranih obješenih fasada objekata bez ograničenja visine.



| Tehnički podaci                     | Vrijednost               | Standard   |
|-------------------------------------|--------------------------|------------|
| Toplinska provodljivost $\lambda_D$ | 0,035 W/mK               | EN 13162   |
| Reakcija na vatru                   | A1                       | EN 13501-1 |
| Otpor strujanju zraka               | $> 10 \text{ kPa s/m}^2$ |            |
| Granična temperatura upotrebe       | 200°C                    |            |

|                                                  |      |      |      |      |      |      |      |      |      |      |
|--------------------------------------------------|------|------|------|------|------|------|------|------|------|------|
| Debljina [mm]                                    | 50   | 80   | 100  | 120  | 140  | 160  | 180  | 200  | 220  | 240  |
| Širina [mm]                                      | 600  | 600  | 600  | 600  | 600  | 600  | 600  | 600  | 600  | 600  |
| Dužina [mm]                                      | 1250 | 1250 | 1250 | 1250 | 1250 | 1250 | 1250 | 1250 | 1250 | 1250 |
| Toplinski otpor $R_D$ [ $\text{m}^2\text{K/W}$ ] | 1,40 | 2,25 | 2,85 | 3,40 | 4,00 | 4,55 | 5,10 | 5,70 | 6,25 | 6,85 |



[www.blauer-engel.de/uz132](http://www.blauer-engel.de/uz132)



Proizvod je certificiran sukladno sa EN 13162.  
Broj EG Certifikata o sukladnosti: 0672 – CPR – 0319.

MW – skraćenica oznaka za mineralnu vunu  
EN 13162 – broj europskog standarda  
Ti – granična odstupanja debljine  
Tri – zatezna čvrstoća okomito na ravninu ploče  
WL(P) – dugotrajno upijanje vode  
MUi – difuzija vodene pare  
SDi – deklarirani stupanj dinamičke krutosti  
Cpi – stišljivost  
AFi – otpor strujanju zraka

